



Essential SmartBright G4 LED Floodlight BVP150

BVP150 LED27/CW PSU 30W SWB G2 CN

Essential SmartBright G4 LED Floodlight BVP150 – 2850 lm – 30 W – 6500 K

The Essential SmartBright G4 LED floodlight comes in a compact and sturdy design. Lightweight, with a robust die-cast aluminum housing and corrosion-proof coating, it's suitable for general outdoor applications. Plus, with a higher efficacy than the previous generation, it also saves more energy.

Product data

General information		Power Factor (Min)	
Light source color	865 cool daylight	0.9	
Driver included	Yes	Controls and dimming	
Optical cover/lens type	Glass	Dimmable	No
Control interface	-	Mechanical and housing	
Connection	Flying leads/wires	Housing Material	Aluminum die-cast
Cable	Cable 0.6 m without plug	Optical cover/lens material	Tempered glass
Protection class IEC	Safety class I	Overall length	185 mm
CE mark	-	Overall width	161 mm
Operating and electrical		Overall height	28 mm
Input Voltage	220–240 V	Effective projected area	0.013 m ²
Input Frequency	50 or 60 Hz	Color	Black
Inrush current	0.78 A		


Essential SmartBright G4 LED Floodlight BVP150

Approval and application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Initial performance (IEC compliant)	
Initial luminous flux (system flux)	2850 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	95 lm/W
Init. Corr. Color Temperature	6500 K
Init. Color Rendering Index	>80
Initial chromaticity	(0.313, 0.337) SDCM <6
Initial input power	30 W
Power consumption tolerance	+/-10%
Application conditions	
Ambient temperature range	-40 to +50 °C

Product data	
Full product code	692382864812199
Order product name	BVP150 LED27/CW PSU 30W SWB G2 CN
EAN/UPC - Product	6923828648121
Order code	911401833083
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24
Material Nr. (12NC)	911401833083
Net Weight (Piece)	0.540 kg



Dimensional drawing



BVP150							
	10W	20W	30W	50W	70W	100W	150W
A	107	141	188	220	273	320	382
B	99	122	155	175	202	246	289
C	29	27	28	30	33	37	40
a	45	75	100	125	125	160	200
b	5	5	6	8,5	8,5	8,5	10,5
c	5,5	5,5	6,5	9	9	9	11

BVP150 LED27/CW PSU 30W SWB G2 CN

