



Essential SmartBright G3 LED Security Light

BVP150 LED42/CW 220-240V 50W SWB MDU CE

Essential SmartBright G3 LED Security Light - 4250 lm - 50 W - 6500 K

The Essential SmartBright G3 LED security light is a motion sensor activated security light, with a built-in PIR sensor and Lux sensor, automatic and instant-on when motion detected, assuring your property is well lit for visibility at night and dusk.


Product data

General Information		Mechanical and Housing	
Light source color	865 cool daylight	Housing Material	Aluminum die cast
Driver included	Yes	Optical cover/lens material	Tempered glass
Optical cover/lens type	-	Overall length	200 mm
Control interface	-	Overall width	194 mm
Connection	Flying leads/wires	Overall height	45 mm
Cable	Cable without plug 3-pole	Color	Black
Protection class IEC	Safety class I	Approval and Application	
CE mark	CE mark	Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Operating and Electrical		Mech. impact protection code	IK06 [1 J]
Input Voltage	220 to 240 V	Initial Performance (IEC Compliant)	
Input Frequency	50 or 60 Hz	Initial luminous flux (system flux)	4250 lm
Power Factor (Min)	0.9	Luminous flux tolerance	+/-10%
Controls and Dimming		Initial LED luminaire efficacy	85 lm/W
Dimmable	No	Init. Corr. Color Temperature	6500 K
		Init. Color Rendering Index	>80


Essential SmartBright G3 LED Security Light

Initial input power	50 W
Power consumption tolerance	+/-10%
Application Conditions	
Ambient temperature range	-25 to +40 °C
Product Data	
Full product code	871016333067999
Order product name	BVP150 LED42/CW 220-240V 50W SWB MDU CE

EAN/UPC - Product	8710163330679
Order code	911401732932
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	911401732932
Net Weight (Piece)	0.920 kg



Dimensional drawing



BVP150/161 Essential Smartbright LED

